



Product data sheet

Issue date: 05/10/23



Wet System flat mop Microsafe

Microfibre and polypropylene flat mop with polyester support for non-slip surfaces and removal of ingrained dirt



Technical information								
code	notes	cm (comm. sizes)	cm (real sizes)	C	pcs	kg	m³	
00000696		J 40 J 14	J 45 J 15		25	3,04	0,019	

SYSTEM

Flat mop system with flaps, to be used with roll, jaw or flat wringer Ideal for washing of non-slip or porous surfaces, suitable to remove ingrained dirt

	GREEN BOX	
Solution (Control of Control of C	EU Ecolabel Certificate	
	DECITEX of the fibres Microfibre: 0,16 DTX	
प्र	Efficient: microfibre requires less chemical to remove dirt and bacteria, reducing water and chemical consumption	
	Wet System Microsafe mop is classified as having a low release of microplastics during washing (test conducted according to DIN EN ISO 4484-1 and 4484-2 by a specialised external laboratory)	





05/10/23

Advantages

- **Time-saving:** thanks to the large cleaning surface and the possibility of reaching corners and cleaning under furniture
- **Ergonomic:** lightweight, it reduces operator's strain
- **Highest hygiene:** microfibre penetrates into the microporosity of the floor, collecting dirt and more than 95% of bacteria

Material

Yarn: 70% microfibre (80% polyester, 20% polyamide) - 30% polypropylene - Support: polyester

Features

Polypropylene inserts for an abrasive action, but respectful of the surfaces

Warnings

Use alkaline detergents with a pH below 11

Washing conditions

Guidelines for proper fibre maintenance

Follow the washing instructions (temperatures and dosage) on the laundry detergent packaging Perform a pre-wash in cold water without laundry detergent to remove any residual product used during cleaning operations

Recommended use of professional textile laundry detergent

Do not use fabric softener

Do not use laundry detergents with Ph> 11

The use of laundry nets is recommended to speed up and make laundry operations more hygienic

Specific mop instructions



Washing temperature max 90° C, recommended 60°



Bleaching possible, do not use chlorine



Tumble dry or in a dryer possible with low program





05/10/23

Related products



Wet System Light frame



Telescopic handle



Action Pro Dry



Dry wringer

Product options



Wet System flat mop Microblue